



Das FG Ölserolabscheidegerät LGA 801 FU / FUW dient zur dezentralen Absaugung von Ölserol in Werkzeugmaschinen. Die FG LGA 801 FU / FUW oil mist collector is used to suck oil mist away locally from machine tools.

Das Ölserolabscheidegerät ist für nichtwasseremischbare Kühlschmierstoffe (Schneidöl, Schleiföl, Bohrlöl) sowie für handelsübliche Ci-Wasser-Emulsionen geeignet. The oil mist collector is suitable for non-water-miscible cooling liquids (cutting oil, grinding oil, drilling oil) as well as commercially available oil-water emulsions.

Das Ölerosolabscheidegerät ist für nichtwasser-mischbare KÜHLSCHMIERSTOFFE (Schneidöl, Schleiföl, Bohröl) sowie für handelsübliche Öl-Wasser-Emulsionen geeignet.
The oil mist collector is suitable for non-water-miscible cooling lubricants (cutting oil, grinding oil, drilling oil) as well as commercial available oil-water emulsions.

Verpackungsart packaging type	Imp-Nr. part no.	72410327		
Code für Auslieferung and delivery code	Code für Auslieferung and delivery code			
Verpackt / sealed	Verpackt / sealed			
Print-Nr. print no.	Imp.-Date imp. date			
Imp.-Date imp. date	Imp.-Date imp. date			
E.L. Anordnungen / labeled directions	E.L. Anordnungen / labeled directions			
				
				
				
				
				
				
				
				
				
				
				
				