



EP 2122
EP 2130
EP 2140 ECO
EP 2155 ECO

Ausführungen:



Modell		EP 2122	EP 2130	EP 2140 ECO	EP 2155 ECO
Spannung	Volt	400		400 *)	
Motorleistung	Watt	2.200	3.000	4.000	5.500
Luftmenge max.	m³/h	330		410	500
Unterdruck	mbar	240 / 300 max.	260 / 340 max.	240 / 300 max.	260 / 320 max.
Filterfläche „M“	m²	2,2 oder 3,2		3,2	
Filterfläche „H“ (H14)	m²	+ 2,0		+ 4,3	
Schmutzbehälter	ltr.	60			
Schutzart		IP 55			
Schalldruckpegel	dB(A)	70		76	
Sauganschluss	Ø mm	80			
Abmessung LxBxH	cm	120 x 68 x 135			
Gewicht	kg	150	160	180	190
Staubklasse M	Art.-Nr.	251-1040	251-1050	251-1060	251-1070
Staubkl. M/Typ22	Art.-Nr.	251-1041	251-1051	251-1061	251-1071
Staubklasse H	Art.-Nr.	251-1042	251-1052	251-1062	251-1072
Staubkl. H/Typ22	Art.-Nr.	251-1043	251-1053	251-1063	251-1073
Upgrade:					
100-I-Schmutzbehälter	Art.-Nr.	053-4042			

*) Direktanlauf (optional mit Stern-Dreieck-Sanft-Anlauf 054-6935 erhältlich)