

**ROBUSTO 1122-LP**  
**ROBUSTO 2115-LP**  
**ROBUSTO 2122-LP**  
**ROBUSTO 2130-LP**  
**ROBUSTO 2155-LP**  
**ROBUSTO 2175-LP**

**Ausführung:**



Modell		ROBUSTO 1122-LP	ROBUSTO 2115-LP	ROBUSTO 2122-LP	ROBUSTO 2130-LP	ROBUSTO 2155-LP	ROBUSTO 2175-LP
Spannung	Volt	230	400			400 *)	400
Motorleistung	Watt	2.200	1.500	2.200	3.000	5.500	7.500
Luftmenge max.	m³/h	310	220	330		480	700
Unterdruck	mbar	220 / 260 max.	200 / 240 max.	240 / 300 max.	260 / 340 max.	260 / 340 max.	260 / 320 max.
Filterfläche „M“	m²	1,75				3,2	
Filterfläche „H“ (H14)	m²	+ 1,7				+ 4,3	
Entsorgung	ltr.	Longopac-System					
Schutzart		IP 55					
Schalldruckpegel	dB(A)	76			77	78	
Sauganschluss	Ø mm	80					
Abmessung LxBxH	cm	94 x 60 x 120 - 163 cm (Höhe Betriebszustand)				110 x 68 x 125 - 173	
Gewicht	kg	140	140	148	150	195	215
<b>Standard-Ausstatt. Staubklasse M</b>	<b>Art.-Nr.</b>	<b>151-3060</b>	<b>251-4137</b>	<b>251-4134</b>	<b>251-4150</b>	<b>251-4180</b>	<b>251-4200</b>
<b>Upgrade Staubkl. H</b>	<b>Art.-Nr.</b>	<b>054-20018</b>				<b>054-2280</b>	
<b>Upgrade GS</b>	<b>Art.-Nr.</b>	<b>054-6435</b>				<b>054-6455</b>	
<b>Upgrade GS + Ex</b>	<b>Art.-Nr.</b>	<b>054-6433</b>				<b>054-6453</b>	
<b>Staubkl. H/Asbest komplett inkl. GS</b>	<b>Art.-Nr.</b>	<b>151-3061</b>	<b>251-4093</b>	<b>251-4103</b>	<b>251-4113</b>	<b>251-4123</b>	<b>251-4133</b>

\*) Direktanlauf (optional mit Stern-Dreieck-Sanft-Anlauf 054-6935 erhältlich)

**bis 3,0 kW:**

**ab 4,0 kW:**

